

View Online at <https://aerobasegroup.com/nsn/5315-01-122-3352>

**First End Style:**

Chamfered

**Second End Style:**

Oval

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.095 inches and 0.097 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.280 inches

**Pinlength:**

Between 2.130 inches and 2.170 inches

**Pindiameter:**

Between 0.2100 inches and 0.2140 inches

**First End Taper Length:**

Between 0.020 inches and 0.060 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

33.0 rockwell c and 38.0 rockwell c

**First End Taper Angle:**

45.0 degrees

**Second End Outer Radius:**

Between 0.470 inches and 0.530 inches

**Special Features:**

Hole located chamfered end

**Material:**

Steel comp 4140

**Material Specification:**

Astm a322 assn standard single material response

**Surface Treatment:**

Phosphate manganese or phosphate zinc

**Surface Treatment Specification:**

Dod-p-16232, type m, class 1 military specification 1st treatment response or dod-p-16232, type z, class 1 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

spec.