

View Online at <https://aerobasegroup.com/nsn/5315-01-122-3352>

First End Style:

Chamfered

Second End Style:

Oval

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.095 inches and 0.097 inches

Distance From Centerline Of Hole To End Of Pin:

0.280 inches

Pinlength:

Between 2.130 inches and 2.170 inches

Pindiameter:

Between 0.2100 inches and 0.2140 inches

First End Taper Length:

Between 0.020 inches and 0.060 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

33.0 rockwell c and 38.0 rockwell c

First End Taper Angle:

45.0 degrees

Second End Outer Radius:

Between 0.470 inches and 0.530 inches

Special Features:

Hole located chamfered end

Material:

Steel comp 4140

Material Specification:

Astm a322 assn standard single material response

Surface Treatment:

Phosphate manganese or phosphate zinc

Surface Treatment Specification:

Dod-p-16232, type m, class 1 military specification 1st treatment response or dod-p-16232, type z, class 1 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

spec.