

View Online at <https://aerobasegroup.com/nsn/5315-01-123-0976>

First End Style:

Square

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.469 inches and 0.499 inches

Shank Length:

Between 0.469 inches and 0.499 inches

Width Between Flats:

0.312 inches

Shoulder Width Across Flats:

0.625 inches

Shank Diameter:

0.312 inches

Overall Length:

Between 2.320 inches and 2.680 inches

Undercut Width:

0.816 inches

Internal Drive Style:

Socket

Second End Relationship With First End:

Identical

Thread Size:

0.312 inches

Second Shank Diameter:

Between 0.550 inches and 0.562 inches

First End Location:

Both ends

Second Shank Length:

Between 0.730 inches and 0.790 inches

Material:

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Undercut

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0