

View Online at <https://aerobasegroup.com/nsn/5315-01-123-7234>

First End Style:

Chamfered

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.095 inches and 0.097 inches

Second Hole Diameter:

Between 0.095 inches and 0.097 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.290 inches and 0.330 inches

Center To Center Distance Between Holes:

Between 1.478 inches and 1.482 inches

Pinlength:

Between 3.280 inches and 3.320 inches

Pindiameter:

Between 0.3100 inches and 0.3120 inches

First End Taper Length:

Between 0.020 inches and 0.060 inches

Second End Relationship With First End:

Identical

Hardness Rating:

30.0 rockwell c and 35.0 rockwell c

First End Taper Angle:

45.0 degrees

Surface Finish:

250.0 microinches

Material:

Steel comp 4140

Material Specification:

Astm a322 assn standard single material response

Surface Treatment:

Phosphate manganese or phosphate zinc

Surface Treatment Specification:

Dod-p-16232, ty m cl 1 military specification 1st treatment response or dod-p-16232, ty z cl 1 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

spec.