## NSN 5315-01-123-7234

Headless Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-123-7234

| First End Style:                                                                                                                             |
|----------------------------------------------------------------------------------------------------------------------------------------------|
| Chamfered                                                                                                                                    |
| Hole Arrangement Style:                                                                                                                      |
| Both end drilled                                                                                                                             |
| First Hole Diameter:                                                                                                                         |
| Between 0.095 inches and 0.097 inches                                                                                                        |
| Second Hole Diameter:                                                                                                                        |
| Between 0.095 inches and 0.097 inches                                                                                                        |
| Distance From Centerline Of Hole To End Of Pin:                                                                                              |
| Between 0.290 inches and 0.330 inches                                                                                                        |
| Center To Center Distance Between Holes:                                                                                                     |
| Between 1.478 inches and 1.482 inches                                                                                                        |
| Pinlength:                                                                                                                                   |
| Between 3.280 inches and 3.320 inches                                                                                                        |
| Pindiameter:                                                                                                                                 |
| Between 0.3100 inches and 0.3120 inches                                                                                                      |
| First End Taper Length:                                                                                                                      |
| Between 0.020 inches and 0.060 inches                                                                                                        |
| Second End Relationship With First End:                                                                                                      |
| Identical                                                                                                                                    |
| Hardness Rating:                                                                                                                             |
| 30.0 rockwell c and 35.0 rockwell c                                                                                                          |
| First End Taper Angle:                                                                                                                       |
| 45.0 degrees                                                                                                                                 |
| Surface Finish:                                                                                                                              |
| 250.0 microinches                                                                                                                            |
| Material:                                                                                                                                    |
| Steel comp 4140                                                                                                                              |
| Material Specification:                                                                                                                      |
| Astm a322 assn standard single material response                                                                                             |
| Surface Treatment:                                                                                                                           |
| Phosphate manganese or phosphate zinc                                                                                                        |
| Surface Treatment Specification:                                                                                                             |
| Dod-p-16232, ty m cl 1 military specification 1st treatment response or dod-p-16232, ty z cl 1 military specification 2nd treatment response |
| Shelf Life:                                                                                                                                  |
| N/a                                                                                                                                          |
| Unit Of Measure:                                                                                                                             |
|                                                                                                                                              |
| Demilitarization:                                                                                                                            |
| No                                                                                                                                           |
| Fiig:                                                                                                                                        |
| A212a0                                                                                                                                       |
|                                                                                                                                              |
|                                                                                                                                              |

## NSN 5315-01-123-7234

Headless Straight Pin - Page 2 of 2



Mil-std (military Standard):

spec.