NSN 5315-01-123-7235

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-123-7235

First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.210 inches
Shank Length:
0.210 inches
Shoulder Width Across Flats:
0.250 inches
Shank Diameter:
0.164 inches
Overall Length:
0.880 inches
Undercut Diameter:
0.123 inches
Undercut Width:
0.050 inches
First End Taper Length:
Any acceptable
Second End Taper Length:
Any acceptable
Second End Relationship With First End:
Not identical
Thread Size:
0.164 inches
Second Shank Diameter:
Between 0.1239 inches and 0.1241 inches
First End Location:
Threaded end
First End Taper Angle:
Between 25.0 degrees and 35.0 degrees
Second End Tip Radius:
Between 0.020 inches and 0.060 inches
Second End Taper Angle:
30.0 degrees
Second Shank Length:
0.560 inches

NSN 5315-01-123-7235

Headless Shoulder Pin - Page 2 of 2



Material:
Steel comp 630
Material Specification:
Ams 5643 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 2 federal specification single treatment response
Style Designator:
Undercut
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A212a0