

View Online at <https://aerobasegroup.com/nsn/5315-01-123-7235>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.210 inches

**Shank Length:**

0.210 inches

**Shoulder Width Across Flats:**

0.250 inches

**Shank Diameter:**

0.164 inches

**Overall Length:**

0.880 inches

**Undercut Diameter:**

0.123 inches

**Undercut Width:**

0.050 inches

**First End Taper Length:**

Any acceptable

**Second End Taper Length:**

Any acceptable

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.164 inches

**Second Shank Diameter:**

Between 0.1239 inches and 0.1241 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

Between 25.0 degrees and 35.0 degrees

**Second End Tip Radius:**

Between 0.020 inches and 0.060 inches

**Second End Taper Angle:**

30.0 degrees

**Second Shank Length:**

0.560 inches

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 2 federal specification single treatment response

**Style Designator:**

Undercut

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0