

View Online at <https://aerobasegroup.com/nsn/5315-01-124-3210>

**First End Style:**

Chamfered

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.120 inches and 1.250 inches

**Shank Length:**

1.250 inches

**Shoulder Diameter:**

0.310 inches

**Shank Diameter:**

Between 0.493 inches and 0.498 inches

**Overall Length:**

2.930 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

0.141 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.150 inches

**First End Taper Length:**

0.045 inches

**Second End Relationship With First End:**

Identical

**Thread Size:**

0.500 inches

**Second Shank Diameter:**

Between 0.493 inches and 0.498 inches

**First End Location:**

Both ends

**First End Taper Angle:**

45.0 degrees

**Second Shank Length:**

1.370 inches

**Material:**

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

**Material Specification:**

Astm a576 assn standard all material responses

**Surface Treatment:**

Cadmium and phosphate

**Surface Treatment Specification:**

Qq-p-416, ty3, cl2 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0