NSN 5315-01-127-1644



Headed Straight Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-127-1644 **Head Style:** Pan no. 2 (r1 not required in item description) **Chamfer Length:** Between 0.077 inches and 0.109 inches Diameter: Between 0.869 inches and 0.871 inches **Under Head Length:** Between 1.928 inches and 1.948 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.161 inches and 0.181 inches Distance From Centerline Of Hole To End Of Pin: 0.196 inches Pin Chamfer Angle: Between 14.5 degrees and 15.5 degrees **Shear Strength:** 90200 double pound **Pin Head Diameter:** Between 1.046 inches and 1.078 inches **Special Features:** Shank end may have either a chamfer or radius at the option of the vendor Height: Between 0.109 inches and 0.141 inches Material: Steel comp 4037 or steel comp 4130 or steel comp 8630 **Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Style Designator:** Straight Shelf Life: N/a **Unit Of Measure:**

Fiig: A212a0

No

Demilitarization:

NSN 5315-01-127-1644

Headed Straight Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.