

View Online at <https://aerobasegroup.com/nsn/5315-01-127-1650>

**Head Diameter:**

Between 0.750 inches and 0.905 inches

**Shank Diameter:**

Between 0.6220 inches and 0.6235 inches

**Ring Handle Diameter:**

1.240 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

W/s: deck machinery; towed array handling equipment; sturgeon class ssn (637); los angeles class ssn (688); virginia class submarine, ssn -774; reels and towing equipment; seawolf class ssn; support equip, c-17a aircraft; ship, ohio class ssn (trident)

**Grip Length:**

Between 3.000 inches and 3.020 inches

**Actuation Type:**

Pull

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

57500 double pounds per square inch

**Shoulder To Head End Distance:**

1.400 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.550 inches and 0.580 inches

**Material:**

Stainless steel

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0