NSN 5315-01-127-7207

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-127-7207

| First End Style: |
|--|
| Chamfered |
| Second End Style: |
| Slotted |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.090 inches |
| Shank Length: |
| 0.090 inches |
| Shoulder Diameter: |
| Between 0.137 inches and 0.142 inches |
| Shank Diameter: |
| 0.112 inches |
| Overall Length: |
| 0.435 inches |
| Undercut Diameter: |
| 0.078 inches |
| Undercut Width: |
| 0.020 inches |
| Second End Slot Width: |
| 0.039 inches |
| First End Taper Length: |
| 0.030 inches |
| Second End Slot Depth: |
| 0.058 inches |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.112 inches |
| First End Location: |
| Chamfered end |
| First End Taper Angle: |
| 45.0 degrees |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a582 federal specification single material response |
| Surface Treatment: |
| Passivate |

NSN 5315-01-127-7207

Headless Shoulder Pin - Page 2 of 2



| Surface Treatment Specification: |
|---|
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Undercut |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A212a0