## NSN 5315-01-128-1646

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-128-1646

First End Style:

Square

Second End Style:

Chamfered

Thread Class:

3a

#### **Thread Direction:**

**Right-hand** 

Thread Length:

0.405 inches

Shank Length:

0.467 inches

Shoulder Width Across Flats:

0.438 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

**Overall Length:** 

Between 0.880 inches and 0.900 inches

#### Second End Taper Length:

Between 0.288 inches and 0.308 inches

### Second End Relationship With First End:

Not identical

Thread Size:

0.190 inches

### Second Shank Diameter:

Between 0.3020 inches and 0.3220 inches

#### First End Location:

Threaded end

Second End Tip Radius:

Between 0.060 inches and 0.090 inches

Second Shank Length:

Between 0.288 inches and 0.308 inches

Material:

Steel comp 302 or steel comp 304 or steel comp 303se

## Material Specification:

Qq-s-763 cond b federal specification 1st material response or qq-s-763 cond b federal specification 2nd material response or mms265

cond b fscm 76301 mfr ref 3rd material response

Surface Treatment:

Passivate

## Style Designator:

Shoulder

Thread Series Designator:

Unjf

# NSN 5315-01-128-1646

Headless Shoulder Pin - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

