NSN 5315-01-128-1649

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-128-1649 First End Style: Square **Second End Style:** Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.405 inches **Shank Length:** Between 0.355 inches and 0.415 inches **Shoulder Width Across Flats:** 0.438 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Overall Length:** Between 1.070 inches and 1.110 inches Second End Taper Length: Between 0.250 inches and 0.270 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches **Second Shank Diameter:** Between 0.2490 inches and 0.2495 inches First End Location: Threaded end Second End Tip Radius: Between 0.060 inches and 0.090 inches **Second Shank Length:** 0.530 inches Material: Steel comp 302 or steel comp 304 or steel comp 303se **Material Specification:** Qq-s-763 cond b federal specification 1st material response or qq-s-763 cond b federal specification 2nd material response or mms265 cond b fscm 76301 mfr ref 3rd material response **Surface Treatment:**

Passivate

Style Designator:

Shoulder

Thread Series Designator:

Unjf

NSN 5315-01-128-1649

Headless Shoulder Pin - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0