

View Online at <https://aerobasegroup.com/nsn/5315-01-131-2464>

First End Style:

Chamfered

Second End Style:

Round

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.000 inches

Shank Length:

1.120 inches

Shoulder Diameter:

Between 0.365 inches and 0.375 inches

Shank Diameter:

0.250 inches

Overall Length:

2.120 inches

First End Taper Length:

0.040 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.250 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Outer Radius:

0.188 inches

Special Features:

Two parallel symmetrical flats on shoulder 0.500 in. Nom lg 0.312 in. Nom w between flats adjacent to thread

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316f or steel comp 316l or steel comp 317 or steel comp 317l or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 303f or steel comp 303s or steel comp 323 or steel comp 324

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0