# NSN 5315-01-131-7704

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-131-7704

## Head Style:

Pan no. 2 (r1 not required in item description)

## Chamfer Length:

Between 0.062 inches and 0.094 inches

## Diameter:

Between 0.745 inches and 0.747 inches

### **Under Head Length:**

Between 3.131 inches and 3.151 inches

## Hole Arrangement Style:

One end drilled

### First Hole Diameter:

Between 0.131 inches and 0.151 inches

## Distance From Centerline Of Hole To End Of Pin:

0.165 inches

#### Hardness Rating:

26.5 rockwell c and 32.0 rockwell c

## Pin Chamfer Angle:

Between 14.5 degrees and 15.5 degrees

## Shear Strength:

66280 double pound

## Pin Head Diameter:

Between 0.859 inches and 0.891 inches

### **Special Features:**

Shank end may have either a chamfer or radius at the option of the vendor

### Height:

Between 0.062 inches and 0.094 inches

### Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

### Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification

3rd material response

### Surface Treatment:

Cadmium and chromate

### **Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

### Style Designator:

Straight

## Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5315-01-131-7704

Headed Straight Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard):

Mil-s-6758 spec.

