NSN 5315-01-133-0058

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-133-0058 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 2b **Thread Direction:** Right-hand Thread Length: 0.440 inches **Shank Length:** 1.255 inches **Shoulder Diameter:** 0.500 inches **Shank Diameter:** 0.373 inches **Overall Length:** 6.130 inches **Undercut Diameter:** 0.300 inches **Undercut Width:** 0.253 inches First End Taper Length: 0.326 inches **Second End Taper Length:** 0.040 inches Thready Qty Per Inch (tpi): Second End Relationship With First End: Not identical **Thread Size:** 0.375 inches **Second Shank Diameter:** 0.319 inches First End Location: Both ends First End Taper Angle: 40.0 degrees First End Tip Radius: 0.100 inches

Surface Finish: 125.0 microinches

NSN 5315-01-133-0058

Headless Shoulder Pin - Page 2 of 2



Second End Taper Angle:
45.0 degrees
Second Shank Length:
4.875 inches
Special Features:
Additional thd on shaft, 0.375-24 unf-2a, 0.463 in. Lg, 3.354 in. From right end of shaft; one pin hole 0.125 in. Diameter and one pin hole
0.157 in. Dia
Material:
Titanium alloy
Material Specification:
Mil-t-9047, cl 5 military specification single material response
Style Designator:
Undercut
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0
Mil-std (military Standard):
Mil-t-9047 spec.