

View Online at <https://aerobasegroup.com/nsn/5315-01-133-7966>

**First End Style:**

Chamfered

**First Step Diameter:**

Between 0.5645 inches and 0.5655 inches

**First Step Length:**

Between 0.690 inches and 0.710 inches

**Second Step Diameter:**

0.376 inches

**Second Step Length:**

1.710 inches

**Third Step Diameter:**

Between 0.373 inches and 0.374 inches

**Third Step Length:**

1.200 inches

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.1250 inches and 0.1257 inches

**Second Hole Diameter:**

Between 0.1250 inches and 0.1257 inches

**Distance From Centerline Of Hole To End Of Pin:**

1.025 inches

**Center To Center Distance Between Holes:**

Between 2.580 inches and 2.590 inches

**First End Taper Length:**

0.040 inches

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**First End Location:**

Both ends

**First End Taper Angle:**

50.0 degrees

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-5000 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response or qq-p-416, type 2, class 3 federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5000 spec.