

View Online at <https://aerobasegroup.com/nsn/5315-01-133-7966>

First End Style:

Chamfered

First Step Diameter:

Between 0.5645 inches and 0.5655 inches

First Step Length:

Between 0.690 inches and 0.710 inches

Second Step Diameter:

0.376 inches

Second Step Length:

1.710 inches

Third Step Diameter:

Between 0.373 inches and 0.374 inches

Third Step Length:

1.200 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.1250 inches and 0.1257 inches

Second Hole Diameter:

Between 0.1250 inches and 0.1257 inches

Distance From Centerline Of Hole To End Of Pin:

1.025 inches

Center To Center Distance Between Holes:

Between 2.580 inches and 2.590 inches

First End Taper Length:

0.040 inches

Second End Relationship With First End:

Identical

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

First End Location:

Both ends

First End Taper Angle:

50.0 degrees

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response or qq-p-416, type 2, class 3 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5000 spec.