

View Online at <https://aerobasegroup.com/nsn/5315-01-136-8288>

**Shank Diameter:**

Between 0.372 inches and 0.374 inches

**Button Handle Diameter:**

Between 0.875 inches and 1.175 inches

**Detent Quantity:**

2

**Lanyard Length:**

4.000 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 1.500 inches and 1.520 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

20000 double pounds per square inch

**Shoulder To Head End Distance:**

1.040 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.335 inches and 0.365 inches

**Material:**

Steel comp 631 spring

**Material Specification:**

Qq-s-763 federal specification single material response handle

**Surface Treatment:**

Passivate shank

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response shank

**Style Designator:**

Button

**Specification Data:**

80063-sm-a-588131 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.