

View Online at <https://aerobasegroup.com/nsn/5315-01-137-7191>

**Shank Diameter:**

Between 0.3095 inches and 0.3110 inches

**Button Handle Diameter:**

Between 0.810 inches and 1.135 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

W/s: support equipment, f-4 aircraft; aircraft, eagle f-15; support equipment, f-16 aircraft

**Grip Length:**

Between 3.000 inches and 3.020 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

14400 double pound

**Shoulder To Head End Distance:**

0.930 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.300 inches and 0.330 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0