

View Online at <https://aerobasegroup.com/nsn/5315-01-138-8006>

**Handle Length:**

Between 1.750 inches and 1.815 inches

**Shank Diameter:**

0.250 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Wsd: submarine ship control and navigation systems; submarine hydraulic systems, support equip, c-17a aircraft; seawolf class ssn; aircraft, b-2 bomber (atb); level 1/subsafe; helicopter, advance attack, ah-1w; trident auxiliary systems; submarine auxillary and miscellaneous systems; austin ship class lpd-4 amphibious transport docks

**Grip Length:**

1.600 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

9200 double pound

**Shoulder To Head End Distance:**

1.270 inches

**Criticality Code Justification:**

Feat

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.260 inches and 0.290 inches

**Special Features:**

Weapon system essential

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0