

View Online at <https://aerobasegroup.com/nsn/5315-01-138-8006>

Handle Length:

Between 1.750 inches and 1.815 inches

Shank Diameter:

0.250 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Wsd: submarine ship control and navigation systems; submarine hydraulic systems, support equip, c-17a aircraft; seawolf class ssn; aircraft, b-2 bomber (atb); level 1/subsafe; helicopter, advance attack, ah-1w; trident auxiliary systems; submarine auxillary and miscellaneous systems; austin ship class lpd-4 amphibious transport docks

Grip Length:

1.600 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

9200 double pound

Shoulder To Head End Distance:

1.270 inches

Criticality Code Justification:

Feat

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Special Features:

Weapon system essential

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0