

View Online at <https://aerobasegroup.com/nsn/5315-01-140-8873>

**Shank Diameter:**

Between 0.1870 inches and 0.1885 inches

**Button Handle Diameter:**

Between 0.720 inches and 0.800 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.300 inches and 1.320 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.830 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.230 inches and 0.260 inches

**Special Features:**

Warning streamer, p/n nas1756-36 and tag, p/n st9m602-1 attached to cable lanyard

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0