NSN 5315-01-141-3706

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-141-3706

| View Online at https://aerobasegroup.com/nsn/5315-01-141-3706 |
|--|
| First End Style: |
| Chamfered |
| Hole Arrangement Style: |
| One end drilled |
| First Hole Diameter: |
| 0.127 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 0.560 inches |
| Pinlength: |
| 4.190 inches |
| Pindiameter: |
| Between 0.3070 inches and 0.3100 inches |
| First End Taper Length: |
| 0.030 inches |
| Second End Relationship With First End: |
| Identical |
| First End Taper Angle: |
| 45.0 degrees |
| Special Features: |
| Heat treat with mil-h-6875 for tensile stength 130000 to 150000 psi |
| Material: |
| Steel comp 4130 or steel comp 4140 |
| Material Specification: |
| Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |
| Mil-std (military Standard): |
| Mil-s-6758 spec. |
| |
| |