

View Online at <https://aerobasegroup.com/nsn/5315-01-148-6867>

First End Style:

Square

Head Style:

Flat

Diameter:

Between 0.4355 inches and 0.4360 inches

Undercut Diameter:

0.375 inches

Under Head Length:

Between 0.941 inches and 0.946 inches

Undercut Width:

0.031 inches

Internal Drive Style:

Torque

Hardness Rating:

46.0 rockwell c and 52.0 rockwell c

Pin Head Diameter:

0.562 inches

Surface Finish:

32.0 microinches outside diameter

Special Features:

Concentric hole at square end 0.594 in. Nom deep, counterbored 0.094 in. Min, 0.099 in. Maximum deep, 0.281 in. Min, 0.291 in. Maximum diameter and threaded 0.138 in.-32 unc-2b, 0.406 in. Nom thread lg

Height:

0.062 inches

Material:

Steel comp 632

Material Specification:

Ams 5657 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 type 1, 2, or 3 federal specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-I-46010 spec.