

View Online at <https://aerobasegroup.com/nsn/5315-01-148-8259>

**First End Style:**

Square

**Head Style:**

Flat

**Diameter:**

Between 0.4355 inches and 0.4360 inches

**Effective Length:**

6.750 inches

**Undercut Diameter:**

Between 0.406 inches and 0.421 inches

**Under Head Length:**

8.083 inches

**Undercut Width:**

5.500 inches

**Second Undercut Width:**

0.062 inches

**Second Undercut Diameter:**

0.406 inches

**Internal Drive Style:**

Torque

**Hardness Rating:**

36.0 rockwell c and 42.0 rockwell c

**Pin Head Diameter:**

0.562 inches

**Surface Finish:**

32.0 microinches outside diameter

**Special Features:**

Undercut at square end 0.078 in. Min, 0.088 in. Maximum long, 0.310 in. Min, 0.311 in. Maximum dia; concentric hole 0.156 in. Min, 0.166 in. Maximum deep, 0.248 in. Min, 0.252 in. Maximum diameter at square end

**Height:**

0.062 inches

**Material:**

Steel comp 630

**Material Specification:**

Aisi, 17-4ph assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 type 1, 2, or 3 federal specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0