
NSN 5315-01-149-9714

Headless Shoulder Pin - Page 1 of 1

First End Style:





First End Style.	
Square	
Shank Length:	
0.219 inches	
Shoulder Diameter:	
Between 0.404 inches and 0.405 inches	
Shank Diameter:	
Between 0.404 inches and 0.405 inches	
Overall Length:	
0.531 inches	
Undercut Diameter:	
Between 0.297 inches and 0.299 inches	
Undercut Width:	
0.093 inches	
Second End Relationship With First End:	
Identical	
First End Location:	
Both ends	
Surface Finish:	
63.0 microinches undercut	
Special Features:	
One hole 0.312 inch min and 0.343 inch maximum deep, bottom tap, 8-32nc-3b or 8-32nc-3	
Material:	
Steel comp 1020	
Material Specification:	
Astm a10 assn standard single material response and astm a575 assn standard single material response	or astm a576 assn standard
single material response	
Surface Treatment:	
Phosphate manganese	
Surface Treatment Specification:	
Dod-p-16232 type m class 1 military specification single treatment response	
Style Designator:	
Undercut	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A212a0	
Mil-std (military Standard):	
spec.	