

View Online at <https://aerobasegroup.com/nsn/5315-01-151-9344>

First End Style:

Chamfered

Second End Style:

Square

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.720 inches and 0.800 inches

Shank Length:

Between 1.270 inches and 1.330 inches

Shoulder Width Across Flats:

0.438 inches

Shank Diameter:

0.250 inches

Overall Length:

Between 2.500 inches and 2.640 inches

First End Taper Length:

Between 0.200 inches and 0.280 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.250 inches

Second Shank Diameter:

Between 0.370 inches and 0.380 inches

First End Location:

Unthreaded end

First End Taper Angle:

30.0 degrees

Criticality Code Justification:

Zzzy

Second Shank Length:

Between 1.070 inches and 1.130 inches

Special Features:

Item must comply with requirements of defense supply center philadelphia production standard po0307nrp

Material:

Steel comp 303

Material Specification:

Aisi assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0