

View Online at <https://aerobasegroup.com/nsn/5315-01-156-8849>

**First End Style:**

Chamfered

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

0.250 inches

**Second Hole Diameter:**

0.250 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.250 inches

**Center To Center Distance Between Holes:**

7.500 inches

**Pinlength:**

8.000 inches

**Pindiameter:**

Between 0.8735 inches and 0.8740 inches

**First End Taper Length:**

0.130 inches

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

32.0 microinches outside diameter

**Special Features:**

Hole located 5.250 in. From end hole on same centerline 0.250 in. Diameter and 0.130 in. Dp; alternate hardness rating rockwell c scale 57.0 min and 62.0 maximum when flame hardened

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8640 or steel comp 8740

**Material Specification:**

Astm a322 assn standard 1st material response or astm a331 assn standard 2nd material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

D0d-p-16232, ty m, cl 4 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

spec.