

View Online at <https://aerobasegroup.com/nsn/5315-01-156-9599>

**Head Diameter:**

Between 0.485 inches and 0.515 inches

**Shank Diameter:**

Between 0.370 inches and 0.373 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.187 inches

**Detent Quantity:**

2

**Grip Length:**

Between 0.600 inches and 0.620 inches

**Actuation Type:**

Push

**Shear Strength:**

10300 double pounds per square inch

**Shoulder To Head End Distance:**

Between 0.380 inches and 0.560 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

Between 0.330 inches and 0.390 inches

**Material:**

Steel comp 303 spindle or steel comp 303 plus x spindle or steel comp 303cu spindle or steel comp 303ma spindle or steel comp 303pb spindle or steel comp 303se spindle or steel comp 304 spindle or steel comp 304l spindle or steel comp 305 spindle or steel comp 309 spindle or steel comp 310 spindle or steel comp 316 spindle or steel comp 316l spindle or steel comp 317 spindle or steel comp 321 spindle or steel comp 322 spindle or steel comp 324 spindle or steel comp 347 spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0