

View Online at <https://aerobasegroup.com/nsn/5315-01-156-9599>

Head Diameter:

Between 0.485 inches and 0.515 inches

Shank Diameter:

Between 0.370 inches and 0.373 inches

Ring Handle Diameter:

Between 1.000 inches and 1.187 inches

Detent Quantity:

2

Grip Length:

Between 0.600 inches and 0.620 inches

Actuation Type:

Push

Shear Strength:

10300 double pounds per square inch

Shoulder To Head End Distance:

Between 0.380 inches and 0.560 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

Between 0.330 inches and 0.390 inches

Material:

Steel comp 303 spindle or steel comp 303 plus x spindle or steel comp 303cu spindle or steel comp 303ma spindle or steel comp 303pb spindle or steel comp 303se spindle or steel comp 304 spindle or steel comp 304l spindle or steel comp 305 spindle or steel comp 309 spindle or steel comp 310 spindle or steel comp 316 spindle or steel comp 316l spindle or steel comp 317 spindle or steel comp 321 spindle or steel comp 322 spindle or steel comp 324 spindle or steel comp 347 spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0