NSN 5315-01-158-8467

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-158-8467

Head Diameter:

29.0 millimeters

Shank Diameter:

Between 17.9 millimeters and 18.0 millimeters

Ring Handle Diameter:

Between 36.0 millimeters and 44.0 millimeters

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 45.0 millimeters and 45.6 millimeters

Actuation Type:

Push

Hardness Rating:

58.0 rockwell c detent and 62.0 rockwell c detent

Shear Strength:

33226 double newtons per square millimeter

Shoulder To Head End Distance:

43.0 millimeters

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

Between 15.9 millimeters and 16.1 millimeters

Material:

Steel comp 630 spindle

Material Specification:

Qq-w-423 federal specification 1st material response spring or ams5673 assn standard 2nd material response spring

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

NSN 5315-01-158-8467

Quick Release Pin - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

