## NSN 5315-01-158-8467

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-158-8467 **Head Diameter:** 29.0 millimeters **Shank Diameter:** Between 17.9 millimeters and 18.0 millimeters **Ring Handle Diameter:** Between 36.0 millimeters and 44.0 millimeters **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 45.0 millimeters and 45.6 millimeters **Actuation Type:** Push **Hardness Rating:** 58.0 rockwell c detent and 62.0 rockwell c detent **Shear Strength:** 33226 double newtons per square millimeter **Shoulder To Head End Distance:** 43.0 millimeters Pin Attachment Type: Ring **Detent To Tapered End Distance:** Between 15.9 millimeters and 16.1 millimeters Material: Steel comp 630 spindle **Material Specification:** Qq-w-423 federal specification 1st material response spring or ams5673 assn standard 2nd material response spring **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A212a0

## NSN 5315-01-158-8467

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.