

View Online at <https://aerobasegroup.com/nsn/5315-01-160-5800>

**Head Diameter:**

Between 0.410 inches and 0.590 inches

**Shank Diameter:**

Between 0.3095 inches and 0.3110 inches

**Ring Handle Diameter:**

1.060 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.400 inches and 1.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

14400 double pounds per square inch

**Shoulder To Head End Distance:**

0.830 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.300 inches and 0.360 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0