

View Online at <https://aerobasegroup.com/nsn/5315-01-160-6333>

First End Style:

Chamfered

Second End Style:

Counterbored w/o through hole

Shoulder Width Across Flats:

0.546 inches

Overall Length:

Between 1.585 inches and 1.615 inches

First Step Diameter:

Between 0.600 inches and 0.620 inches

First Step Length:

Between 0.038 inches and 0.042 inches

Second Step Diameter:

Between 0.5459 inches and 0.5461 inches

Second Step Length:

Between 0.620 inches and 0.640 inches

Third Step Diameter:

Between 0.4722 inches and 0.4820 inches

Third Step Length:

Between 0.500 inches and 0.540 inches

Second End Counterbore Diameter:

Between 0.323 inches and 0.333 inches

Second End Counterbore Depth:

Between 0.940 inches and 0.960 inches

First End Taper Length:

Between 0.040 inches and 0.060 inches

Second End Relationship With First End:

Not identical

First End Location:

Chamfered end

First End Taper Angle:

Between 28.0 degrees and 32.0 degrees

Criticality Code Justification:

Feat

Special Features:

Dia of shank opposite cbore is 0.4362 min, 0.4364 max; both first and second step diameters are finished to a slightly smaller diameter for part of their length

Material:

Nickel alloy

Material Specification:

Ams 5663 assn standard single material response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0