

View Online at <https://aerobasegroup.com/nsn/5315-01-160-6333>

**First End Style:**

Chamfered

**Second End Style:**

Counterbored w/o through hole

**Shoulder Width Across Flats:**

0.546 inches

**Overall Length:**

Between 1.585 inches and 1.615 inches

**First Step Diameter:**

Between 0.600 inches and 0.620 inches

**First Step Length:**

Between 0.038 inches and 0.042 inches

**Second Step Diameter:**

Between 0.5459 inches and 0.5461 inches

**Second Step Length:**

Between 0.620 inches and 0.640 inches

**Third Step Diameter:**

Between 0.4722 inches and 0.4820 inches

**Third Step Length:**

Between 0.500 inches and 0.540 inches

**Second End Counterbore Diameter:**

Between 0.323 inches and 0.333 inches

**Second End Counterbore Depth:**

Between 0.940 inches and 0.960 inches

**First End Taper Length:**

Between 0.040 inches and 0.060 inches

**Second End Relationship With First End:**

Not identical

**First End Location:**

Chamfered end

**First End Taper Angle:**

Between 28.0 degrees and 32.0 degrees

**Criticality Code Justification:**

Feat

**Special Features:**

Dia of shank opposite cbore is 0.4362 min, 0.4364 max; both first and second step diameters are finished to a slightly smaller diameter for part of their length

**Material:**

Nickel alloy

**Material Specification:**

Ams 5663 assn standard single material response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0