

View Online at <https://aerobasegroup.com/nsn/5315-01-162-0425>

First End Style:

Slotted

Head Style:

L shape

Head Length:

Between 0.400 inches and 0.420 inches

Under Head Length:

2.125 inches

First Step Diameter:

Between 0.245 inches and 0.250 inches

First Step Length:

1.563 inches

Second Step Diameter:

Between 0.215 inches and 0.220 inches

Second Step Length:

0.562 inches

Head Width:

Between 0.975 inches and 0.985 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.078 inches and 0.083 inches

Distance From Centerline Of Hole To End Of Pin:

0.125 inches

First End Slot Width:

Between 0.037 inches and 0.047 inches

First End Slot Depth:

0.501 inches

Special Features:

0.125 in. Diameter hole in end must be perpendicular to slot; head tapered on a plane from 0.410 in. Diameter to 0.300 in. Diameter on length

Height:

0.312 inches

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Ps13105, fscm 76301 mfr ref single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0