

View Online at <https://aerobasegroup.com/nsn/5315-01-162-0425>

**First End Style:**

Slotted

**Head Style:**

L shape

**Head Length:**

Between 0.400 inches and 0.420 inches

**Under Head Length:**

2.125 inches

**First Step Diameter:**

Between 0.245 inches and 0.250 inches

**First Step Length:**

1.563 inches

**Second Step Diameter:**

Between 0.215 inches and 0.220 inches

**Second Step Length:**

0.562 inches

**Head Width:**

Between 0.975 inches and 0.985 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.078 inches and 0.083 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.125 inches

**First End Slot Width:**

Between 0.037 inches and 0.047 inches

**First End Slot Depth:**

0.501 inches

**Special Features:**

0.125 in. Diameter hole in end must be perpendicular to slot; head tapered on a plane from 0.410 in. Diameter to 0.300 in. Diameter on length

**Height:**

0.312 inches

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

Ps13105, fscm 76301 mfr ref single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0