

View Online at <https://aerobasegroup.com/nsn/5315-01-162-5133>

**First End Style:**

Countersunk

**Second End Style:**

Chamfered and countersunk

**Shank Length:**

Between 0.055 inches and 0.085 inches

**Shoulder Diameter:**

Between 0.4006 inches and 0.4011 inches

**Shank Diameter:**

Between 0.380 inches and 0.400 inches

**Overall Length:**

1.400 inches

**Undercut Diameter:**

Between 0.240 inches and 0.260 inches

**Undercut Width:**

Between 0.140 inches and 0.160 inches

**Second End Taper Length:**

Between 0.040 inches and 0.060 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Second End Countersink Angle:**

Between 55.0 degrees and 65.0 degrees

**First End Location:**

Shank end

**Criticality Code Justification:**

Aavh

**First End Countersink Angle:**

Between 55.0 degrees and 65.0 degrees

**First End Countersink Diameter:**

0.170 inches

**Second End Taper Angle:**

Between 28.0 degrees and 32.0 degrees

**Second End Countersink Diameter:**

0.170 inches

**Special Features:**

Countersunk holes 0.160 in. Dp

**Material:**

Steel

**Material Specification:**

Ams5613 assn standard single material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

Ams2406 assn standard single treatment response

**Style Designator:**

Undercut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0