## NSN 5315-01-162-5136

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-162-5136

| First End Style:  |
|---|
| Chamfered   |
| Second End Style:   |
| Square  |
| Shank Length:   |
| 0.070 inches  |
| Shoulder Diameter:  |
| Between 0.7225 inches and 0.7230 inches                   |
| Shank Diameter:   |
| Between 0.500 inches and 0.520 inches                     |
| Overall Length:   |
| Between 2.210 inches and 2.230 inches                     |
| Undercut Diameter:  |
| Between 0.310 inches and 0.330 inches                     |
| Undercut Width:   |
| Between 0.075 inches and 0.085 inches                     |
| First End Taper Length:                                   |
| Between 0.040 inches and 0.060 inches                     |
| Second End Relationship With First End:                   |
| Not identical   |
| Hardness Rating:  |
| 30.0 rockwell c and 38.0 rockwell c                       |
| First End Location:                                       |
| Shoulder end  |
| First End Taper Angle:                                    |
| Between 28.0 degrees and 32.0 degrees                     |
| Criticality Code Justification:                           |
| Aavh  |
| Special Features:   |
| 0.375 in. Dia, 1.910 in. Dp hole centered in shoulder end |
| Material:   |
| Steel   |
| Material Specification:                                   |
| Ams5613 assn standard single material response            |
| Surface Treatment:  |
| Chromium  |
| Surface Treatment Specification:                          |
| Ams2406 assn standard single treatment response           |
| Style Designator:   |
| Undercut  |
| Shelf Life:   |
| N/a   |

## NSN 5315-01-162-5136

Headless Shoulder Pin - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

