

View Online at <https://aerobasegroup.com/nsn/5315-01-165-8837>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered and counterbored

**Overall Length:**

1.875 inches

**Diameter:**

Between 0.7501 inches and 0.7503 inches

**Effective Length:**

1.625 inches

**Undercut Diameter:**

Between 0.617 inches and 0.618 inches

**Undercut Width:**

Between 0.076 inches and 0.080 inches

**Second End Counterbore Diameter:**

Between 0.314 inches and 0.324 inches

**Second End Counterbore Depth:**

1.250 inches

**First End Taper Length:**

Any acceptable

**Second End Taper Length:**

Any acceptable

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

30.0 rockwell c and 35.0 rockwell c

**First End Location:**

Grooved end

**First End Taper Angle:**

Between 10.0 degrees and 15.0 degrees

**Surface Finish:**

32.0 microinches outside diameter

**Second End Taper Angle:**

Between 10.0 degrees and 15.0 degrees

**Special Features:**

Hole threaded 0.312-18 unc 2b entire lg

**Material:**

Steel or steel comp 4140

**Surface Treatment:**

Phosphate manganese

**Surface Treatment Specification:**

Dod-p-16232, ty m, cl 1 military specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

spec.