NSN 5315-01-166-6216

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-166-6216 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.600 inches **Shank Length:** 1.250 inches **Shoulder Diameter:** 0.630 inches **Shank Diameter:** Between 0.370 inches and 0.375 inches **Overall Length:** 3.200 inches First End Taper Length: 0.040 inches **Second End Taper Length:** 0.130 inches Second End Relationship With First End: Not identical **Thread Size:** 0.375 inches **Second Shank Diameter:** 0.375 inches **First End Location:** Threaded end First End Taper Angle: 45.0 degrees **Second End Taper Angle:** 30.0 degrees **Second Shank Length:** 1.850 inches

Special Features:

Temper t73 per ss8043, flats on shoulder, 0.380 in. Nom width across flats

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-225/9 federal specification single material response

NSN 5315-01-166-6216

Headless Shoulder Pin - Page 2 of 2

Mil-a-8625 spec.



Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 type 1 military specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0
Mil-std (military Standard):