## NSN 5315-01-166-6216

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-166-6216

First End Style: Chamfered

Second End Style:

Chamfered

Thread Class:

3a

## **Thread Direction:**

**Right-hand** 

Thread Length:

0.600 inches

Shank Length:

1.250 inches

Shoulder Diameter:

0.630 inches

Shank Diameter:

Between 0.370 inches and 0.375 inches

**Overall Length:** 

3.200 inches

First End Taper Length:

0.040 inches

Second End Taper Length:

0.130 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.375 inches

Second Shank Diameter:

0.375 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Taper Angle:

30.0 degrees

Second Shank Length:

1.850 inches

**Special Features:** 

Temper t73 per ss8043, flats on shoulder, 0.380 in. Nom width across flats

Material:

Aluminum alloy 7075

**Material Specification:** 

Qq-a-225/9 federal specification single material response

## NSN 5315-01-166-6216

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 1 military specification single treatment response

Style Designator:

Shoulder

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.