NSN 5315-01-169-4463

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-169-4463

First End Style:		
Countersunk		
Second End Style:		
Slotted		
Shank Length:		
3.813 inches		
Shoulder Diameter:		
0.750 inches		
Shank Diameter:		
Between 0.496 inches and 0.498 inches		
Overall Length:		
4.625 inches		
Hole Arrangement Style:		
One end drilled		
First Hole Diameter:		
Between 0.250 inches and 0.251 inches		
Distance From Centerline Of Hole To End Of Pin:		
0.250 inches		
Second End Slot Width:		
Between 0.250 inches and 0.255 inches		
Second End Slot Depth:		
0.625 inches		
Second End Relationship With First End:		
Not identical		
First End Location:		
Long end		
Surface Finish:		
63.0 microinches long shank		
First End Countersink Diameter:		
0.125 inches		
Special Features:		
Two symmetrical flatson shoulder 0.625 in. Nom lg 0.495 in. Min 0.500 in. Maximum w		
Material:		
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316		
Material Specification:		
Aisi assn standard all material responses		
Surface Treatment:		
Passivate		
Surface Treatment Specification:		
Qq-p-35 federal specification all treatment responses		
Style Designator:		
Shoulder		

NSN 5315-01-169-4463

Headless Shoulder Pin - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0