

View Online at <https://aerobasegroup.com/nsn/5315-01-169-7647>

Shank Diameter:

Between 0.6220 inches and 0.6235 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.300 inches and 1.320 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Shear Strength:

51200 double pound

Shoulder To Head End Distance:

1.700 inches

Pin Center To Handle End Distance:

Between 2.385 inches and 3.070 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.550 inches and 0.580 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-s-6758 military specification single material response spindle or mil-t-6736 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

L handle

Specification Data:

96906-ms17986-1012 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.