

View Online at <https://aerobasegroup.com/nsn/5315-01-169-7647>

**Shank Diameter:**

Between 0.6220 inches and 0.6235 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.300 inches and 1.320 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Shear Strength:**

51200 double pound

**Shoulder To Head End Distance:**

1.700 inches

**Pin Center To Handle End Distance:**

Between 2.385 inches and 3.070 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.550 inches and 0.580 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-s-6758 military specification single material response spindle or mil-t-6736 military specification single material response spindle

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

L handle

**Specification Data:**

96906-ms17986-1012 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.