

View Online at <https://aerobasegroup.com/nsn/5315-01-169-8340>

First End Style:

Chamfered

Head Style:

Flat countersunk undercut

Diameter:

Between 76.51 millimeters and 76.63 millimeters

Effective Length:

44.0 millimeters

Undercut Diameter:

72.57 millimeters

Under Head Length:

151.0 millimeters

Undercut Radius:

Between 12.0 millimeters and 14.0 millimeters

Hole Arrangement Style:

One end drilled

First Hole Diameter:

6.0 millimeters

Distance From Centerline Of Hole To End Of Pin:

94.0 millimeters

Grip Length:

57.0 millimeters

Hardness Rating:

58.0 rockwell c shank

First End Taper Angle:

20.0 degrees

Pin Head Diameter:

Between 89.05 millimeters and 89.55 millimeters

Surface Finish:

1.6 microns head outside diameter

Special Features:

6.0 mm diameter hole on shaft is 21.0 mm min and 24.0 mm maximum deep; two holes on head bearing surface are 11.0 mm diameter and 32.0 mm deep and are tapped 0.500 in. 13-2b unc; one hole on head bearing surface is 8.5 mm min diameter and 9.1 mm maximum diameter and 95.0 mm deep and tapped 0.125 in. 27-2b npsf

Height:

Between 32.0 millimeters and 34.0 millimeters

Material:

Steel comp 1045

Material Specification:

1e361, fscm 11083 mfr ref single material response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0