

View Online at <https://aerobasegroup.com/nsn/5315-01-169-8340>

**First End Style:**

Chamfered

**Head Style:**

Flat countersunk undercut

**Diameter:**

Between 76.51 millimeters and 76.63 millimeters

**Effective Length:**

44.0 millimeters

**Undercut Diameter:**

72.57 millimeters

**Under Head Length:**

151.0 millimeters

**Undercut Radius:**

Between 12.0 millimeters and 14.0 millimeters

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

6.0 millimeters

**Distance From Centerline Of Hole To End Of Pin:**

94.0 millimeters

**Grip Length:**

57.0 millimeters

**Hardness Rating:**

58.0 rockwell c shank

**First End Taper Angle:**

20.0 degrees

**Pin Head Diameter:**

Between 89.05 millimeters and 89.55 millimeters

**Surface Finish:**

1.6 microns head outside diameter

**Special Features:**

6.0 mm diameter hole on shaft is 21.0 mm min and 24.0 mm maximum deep; two holes on head bearing surface are 11.0 mm diameter and 32.0 mm deep and are tapped 0.500 in. 13-2b unc; one hole on head bearing surface is 8.5 mm min diameter and 9.1 mm maximum diameter and 95.0 mm deep and tapped 0.125 in. 27-2b npsf

**Height:**

Between 32.0 millimeters and 34.0 millimeters

**Material:**

Steel comp 1045

**Material Specification:**

1e361, fscm 11083 mfr ref single material response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0