

View Online at <https://aerobasegroup.com/nsn/5315-01-170-4687>

**Head Style:**

Round w/wrench flats

**Chamfer Length:**

0.031 inches

**Slot Width:**

Between 0.190 inches and 0.200 inches

**Slot Length:**

0.812 inches

**Diameter:**

Between 0.498 inches and 0.499 inches

**Under Head Length:**

3.406 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.188 inches and 0.189 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.250 inches

**Width Across Flats:**

0.750 inches

**Hardness Rating:**

38.0 rockwell c and 42.0 rockwell c

**Pin Chamfer Angle:**

45.0 degrees

**Pin Head Diameter:**

1.625 inches

**Surface Finish:**

63.0 microinches outside diameter

**Special Features:**

Full radius on head both ends, two symmetrical flats 0.438 in. O/a w 0.812 in nom lg, 0.062 in. W 0.469 in. Diameter groove on shank adjacent to the head

**Height:**

0.250 inches

**Material:**

Steel comp 4140

**Material Specification:**

Mil-c-6021, cl 2b gr d military specification single material response or mil-s-22141 military specification single material response

**Surface Treatment:**

Phosphate manganese and lubricant

**Surface Treatment Specification:**

Dod-p-16232, ty m cl 3 military specification 1st treatment response and mil-l-46010 military specification 2nd treatment response

**Style Designator:**

Straight

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-c-6021 spec.