

View Online at <https://aerobasegroup.com/nsn/5315-01-170-4687>

Head Style:

Round w/wrench flats

Chamfer Length:

0.031 inches

Slot Width:

Between 0.190 inches and 0.200 inches

Slot Length:

0.812 inches

Diameter:

Between 0.498 inches and 0.499 inches

Under Head Length:

3.406 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.188 inches and 0.189 inches

Distance From Centerline Of Hole To End Of Pin:

0.250 inches

Width Across Flats:

0.750 inches

Hardness Rating:

38.0 rockwell c and 42.0 rockwell c

Pin Chamfer Angle:

45.0 degrees

Pin Head Diameter:

1.625 inches

Surface Finish:

63.0 microinches outside diameter

Special Features:

Full radius on head both ends, two symmetrical flats 0.438 in. O/a w 0.812 in nom lg, 0.062 in. W 0.469 in. Diameter groove on shank adjacent to the head

Height:

0.250 inches

Material:

Steel comp 4140

Material Specification:

Mil-c-6021, cl 2b gr d military specification single material response or mil-s-22141 military specification single material response

Surface Treatment:

Phosphate manganese and lubricant

Surface Treatment Specification:

Dod-p-16232, ty m cl 3 military specification 1st treatment response and mil-l-46010 military specification 2nd treatment response

Style Designator:

Straight

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-c-6021 spec.